# Flat suction cup (round)

SUF 20 NBR-ESD-55 G1/8-IG

Part no..:10.01.01.14127

https://www.schmalz.com/10.01.01.14127


Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Flat Suction Cups (Round) > Flat Suction Cups SUF > SUF 20 NBR-ESD-55 G1/8-IG

## Flat suction cup (round) for process safe handling of smooth or slightly rough surfaces



- Size: 20
- Suction cup material: Nitrile rubber NBR-ESD
- Material hardness [Shore A]: 55 Shore A
- Vacuum connection: G1/8"-F

## Design Data




| Attribute | Value |
|---|---|
| Dmax(S) | 22.80 mm |
| Ds | 20 mm |
| dn | 3.10 mm |
| G1 | G1/8"-F |
| H | 23.50 mm |
| LG1 | 8 mm |
| SW1 | 14 mm |
| Z (Stroke) | 2 mm |

## Technical Data

| Attribute | Value |
|---|---|
| Suction force (-600mbar) | 15 N |
| Pull-off force | 15 N |
| Volume | 0.50 cm³ |
| Curve radius (min) (convex) | 20 mm |
| Hose diameter (rec.) d | 4 mm |
| Size | 20 |
| Suction cup material | Nitrile rubber NBR-ESD |
| Material hardness [Shore A] | 55 Shore A |

Contact Schmalz
Schmalz Inc. | 5850 Oak Forest Drive, Raleigh, NC 27616, United States | +1 (919) 713-0880 |
schmalz.us@schmalz.com

# Flat suction cup (round)

SUF 20 NBR-ESD-55 G1/8-IG

Part no..:10.01.01.14127

https://www.schmalz.com/10.01.01.14127

| | |
|---|---|
| Weight | 6.50 g |
| Product family | SUF |
| Number of folds | 0 |

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m

## Spare parts



**SC 030 G1/8-IG**

Part no..:10.01.06.04307

| |
|---|
| Connection geometry: 030 |
| Vacuum connection: G1/8"-F |
| Fitting length: 14 mm |
| Nominal diameter dn: 3.1 mm |



**SUF 20 NBR-ESD-55 SC030**

Part no..:10.01.01.14036

| |
|---|
| Size: 20 |
| Suction cup material: Nitrile rubber NBR-ESD |
| Material hardness [Shore A]: 55 Shore A |