

TE Internal #: 2229293-1

DC Jack Connectors, Board-to-Board, 7 Position, .079 in [2 mm] Centerline, Receptacle, 30 VDC, Vertical, Printed Circuit Board,

Signal, Board Mount

View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors



Connector System: Board-to-Board

Number of Positions: 7

Centerline (Pitch): 2 mm [.079 in]

Connector & Housing Type: Receptacle

Operating Voltage: 30 VDC

Features

Product Type Features

Connector System	Board-to-Board
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	

Configuration Features

Number of Positions	7
PCB Mount Orientation	Vertical

Electrical Characteristics

Operating Voltage	30 VDC	
-------------------	--------	--

Body Features

Contact Features

Contact Mating Area Plating Material	Gold
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	6 A

Mechanical Attachment

PCB Mount Retention	Without	



Housing Features

Housing Material	Thermoplastic
Centerline (Pitch)	2 mm[.079 in]

Usage Conditions

Operating Temperature Range	-20 - 80 °C[-4 - 176 °F]

Operation/Application

Circuit Application	Signal	
Industry Standards		

Industry Standards

UL Flammability Rating	UL 94V-0	

Packaging Features

Packaging Quantity	900
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



















Documents

Product Drawings

2mm pitch Battery Rec. Assy. 7Pos. H=4.0

English

DC Jack Connectors, Board-to-Board, 7 Position, .079 in [2 mm] Centerline, Receptacle, 30 VDC, Vertical, Printed Circuit Board, Signal, Board Mount



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2229293-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2229293-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2229293-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Product Specifications

Product Specification

English