

Specification Sheet

Part Number: 151-03095



Mount and tie combination makes it easy to service bundles in the field.

Eliminates the need for multiple sized diameter clamps.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.

Standard Torque Cable Tie Mount, Mtg Hole Dia. 0.25", Max Torque 115.0 in lbs, PA666V0, Black, 500/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 151-03095                                                                                                                                                                                                                                                                                                                                         |
| Type                | HDM250                                                                                                                                                                                                                                                                                                                                            |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                        |
| Quantity Per        | carton                                                                                                                                                                                                                                                                                                                                            |
| Product Description | These mounts contain a small tab inside the mounting hole to temporarily engage the threads, allowing assemblers to preinstall the mount on a stud before securing with a washer and a nut. For use with HellermannTyton heavy duty T120, T150 or Wide Strap Cable Ties. Low fire hazard material is designed specifically for rail applications. |
| Short Description   | Standard Torque Cable Tie Mount, Mtg Hole Dia. 0.25", Max Torque 115.0 in lbs, PA666V0, Black, 500/pkg                                                                                                                                                                                                                                            |

|                                     |                               |
|-------------------------------------|-------------------------------|
| Global Part Name                    | HDM250-PA666V0-BK             |
| Length L (Imperial)                 | 1.41                          |
| Length L (Metric)                   | 36.3                          |
| Fixation Method                     | Screw Mounting and Rivet      |
| Width W (Imperial)                  | 0.76                          |
| Width W (Metric)                    | 19.3                          |
| Height H (Imperial)                 | 0.67                          |
| Height H (Metric)                   | 17.0                          |
| Cable Tie Width Max (Imperial)      | 0.5                           |
| Cable Tie Width Max (Metric)        | 12.7                          |
| Mounting Hole Diameter D (Imperial) | 0.25                          |
| Mounting Hole Diameter D (Metric)   | 6.2 mm                        |
| Stud Diameter (Metric)              | 6.2 mm                        |
| Stud Diamater (Imperial)            | 0.24                          |
| Material                            | Polyamide 6.6/6, V0 (PA666V0) |

|                              |                                                       |
|------------------------------|-------------------------------------------------------|
| Material Shortcut            | PA666V0                                               |
| Flammability                 | UL 94 V-0                                             |
| Halogen Free                 | Yes                                                   |
| UV Resistant (Yes/No)        | No                                                    |
| Operating Temperature        | -40°F to +248°F (-40°C to +120°C)                     |
| Maximum Torque (kgf-cm)      | 132.45                                                |
| Maximum Torque (lbf-ft)      | 9.58                                                  |
| Reach Compliant (Article 33) | No                                                    |
| ROHS Compliant               | Yes                                                   |
| Certification/Specification  | ASTM 1354 ASTM E 162 ASTM E 662 Exova   NFPA130: 2017 |
| Package Quantity (Imperial)  | 500                                                   |
| Package Quantity (Metric)    | 500                                                   |
| Customs Number               | 3926909988                                            |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global

customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin.  
([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).