

Part Number: 190060001 Product Description: Avikrimp Quick

Product Description: Avikrimp Quick Disconnect, Female Flag, for 18-22 AWG (0.80-0.35mm<sup>2</sup>) Wire, Tab 6.35 x 0.81mm, Red, Bag

Series Number: 19006 Status: Active

Product Category: Quick Disconnects Engineering Number: AA-5220

#### **Documents & Resources**

#### **Drawings**

Drawing 190060001\_sd.pdf

3D Models and Design Files

3D Model 190060001\_stp.zip

#### **Specifications**

Product Specification PS-19902-011-001.pdf Product Specification PS-19902-013-001.pdf Product Specification PS-19902-014-001.pdf

### **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## **Part Details**

## General

Status	Active
Category	Quick Disconnects
Series	19006
Description	Avikrimp Quick Disconnect, Female Flag, for 18-22 AWG (0.80-0.35mm²) Wire, Tab 6.35 x 0.81mm, Red, Bag
Product Family	Standard Quick-Disconnect Terminals
Product Name	Avikrimp
Type	Quick Disconnect
UPC	800753030886

# Agency

CSA	LR18689
UL	E79133

### Electrical

Voltage - Maximum	600V
-------------------	------

# Physical

Barrel Type	Closed
Color - Resin	Red
Flammability	94V-2
Gender	Female
Glow-Wire Capable	Yes
Insulated	Fully
Insulation	Nylon (PA)
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Tin

Material - Plating Termination	Tin
Material - Resin	Nylon
Net Weight	1.377/g
Orientation	Flag
Packaging Type	Bag
Polarized to Mating Part	No
Tab Thickness	0.81mm
Tab Width	6.35mm
Temperature Range - Operating	-65° to +105°C
Wire Insulation Diameter	3.81mm max.
Wire Size (AWG)	18, 20, 22

### **Solder Process Data**

Lead-Free Process Capability	N/A
------------------------------	-----

# **Application Tooling**

### Global

Description	Part Number
PremiumGrade Hand Crimp Tool for Avikrimp Fully Pre-Insulated and Insulated Quick Disconnect Flags, 14-22 AWG	<u>640014300</u>
Crimp Head for the AT-200 Pneumatic Hand Tool	640054300

This document was generated on Jun 04, 2024