



**NOTES:**

1. SHIPPED ASSEMBLED.
2.  $\varnothing 0.04$  [1.0mm] X 0.06 [1.5mm] DEEP HOLE IN PIN FOR SOLDERING.
3. MATERIALS:  
HOUSING AND LOCKRING - ZINC ALLOY, NICKEL PLATED  
FLEX RELIEF - THERMOPLASTIC, BLACK  
INSERT - THERMOPLASTIC, BLACK  
PINS - COPPER ALLOY, TIN PLATED  
CABLE CLAMP - STEEL, NICKEL PLATED  
SCREW - STEEL, NICKEL PLATED
4. THESE PRODUCTS ARE RoHS COMPLIANT.
- (B) 5. SCREW DRIVE MAY BE SLOTTED, CROSS RECESS, T8, COMBINATION SLOTTED/CROSS RECESS OR COMBINATION SLOTTED/T8.

**CUSTOMER DRAWING**

REV	ECO NUMBER	DATE	BY	APVD
B	28667	3/28/24	PC	TJK
A	26000	3/3/06	TJK	TJK

REVISIONS

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES [mm]  
- TWO PLACE DECIMALS  $\pm 0.02$  [0.5]  
- THREE PLACE DECIMALS  $\pm 0.005$  [0.13]

**DO NOT SCALE DRAWING**

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
SIZE	WIDTH	MULT	LBS/M	TEMPER					
FINISH					MATERIAL				
SPEC No.					SPEC No.				
FIRST USED ON			SCALE		<b>Switchcraft</b> <sup>®</sup>				
			3:2						
DATE DRAWN	BY	CHKD TO	APVD	TJK					
24-May-13	TO	5-28-13	2-29-13		SHEET 1 OF 1				
NAME				PART No.		REV			
MALE DIN 3-8 PIN LOCKING CORD PLUG CONNECTOR, RoHS				05CL_MX, 09CL_MX, 12CL_MX, 15CL_MX SERIES		B			

**SolidWorks CAD File** (B)