# W51-AB21B2-12 - ACTIVE

TE Internal #: 6-1423673-4 Circuit Breakers, Thermal, Trip-Free - Switchable, Illuminated, Red, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 12A Current Rating, 1 Pole

# View on TE.com >



Relays & Contactors > Circuit Breakers



# Circuit Breaker Type: Thermal

Circuit Function: Trip-Free - Switchable

Illuminated: With

Actuator Color: Red

Operating Voltage: 125 VAC

# Features

# **Product Type Features**

Circuit Breaker Style	Contoured Button
Actuator Type	Rocker
Circuit Breaker Type	Thermal
Illuminated	With

# **Configuration Features**

Panel Cutout Size	28.5 x 13.5 mm[1.122 x .531 in]
Circuit Function	Trip-Free - Switchable
Number of Poles	1
Electrical Characteristics	
Operating Voltage	50 VDC
Current Rating	12 A
Interrupt Capacity	1000A @ 250VAC/50VDC
Body Features	
Body Features Actuator Color	Red
	Red
Actuator Color	Red 4 - 40 seconds
Actuator Color Contact Features	

# W51-AB21B2-12

Circuit Breakers, Thermal, Trip-Free - Switchable, Illuminated, Red, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 12A Current Rating, 1 Pole



# Mechanical Attachment Mounting Options Snaps Into 1.122 x .531 (28.5 x 13.5) Panel Cutout Dimensions Panel Thickness (Recommended) .75 - 3 mm[.03 - .118 in] Identification Marking Stamped Marking Type RESET/OFF Molded Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU Compliant with Exemptions

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

EU REACH Regulation (EC) No. 1907/2006

Restricted Materials Above Threshold Current ECHA Candidate List: JAN 2024

(240)

Not Compliant

Candidate List Declared Against: JUL 2021

(219)

SVHC > Threshold:

Cadmium oxide (11.48% in Component)

### Article Safe Usage Statements:

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Not Yet Reviewed for halogen content

Solder Process Capability

Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**

# W51-AB21B2-12

Circuit Breakers, Thermal, Trip-Free - Switchable, Illuminated, Red, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 12A Current Rating, 1 Pole





# Customers Also Bought



UOP	IVIIINI	UIVINL CA	AP HSG
-----	---------	-----------	--------



# Documents

## **CAD** Files

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_6-1423673-4\_F.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_6-1423673-4\_F.3d\_igs.zip

English

**C** For support call +1 800 522 6752

# W51-AB21B2-12

Circuit Breakers, Thermal, Trip-Free - Switchable, Illuminated, Red, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 12A Current Rating, 1 Pole



Customer View Model ENG\_CVM\_CVM\_6-1423673-4\_F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages W51 Rocker-Actuated Thermal Circuit Breaker/Power Switch With Optional Indicator Lamp

English

Agency Approvals CCC Certificate

English