

### AMPLIMITE | AMPLIMITE HD-20

TE Internal #: 5745410-7

PCB D-Sub Connectors, Plug, Board-to-Board, 9 Position, 2.77 mm

[.109 in] Centerline, 2 Row, 1 Connector Shell Size, Square,

AMPLIMITE HD-20

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Plug Assembly: Standard, Vertical, Shell Size 1, 2.74mm



Connector & Housing Type: Plug Connector System: Board-to-Board

Number of Positions: 9

Centerline (Pitch): 2.77 mm [ .109 in ]

Number of Rows: 2

All D-Sub Plug Assembly: Standard, Vertical, Shell Size 1, 2.74mm (50)

## **Features**

Product Type Features	
Shell Material Configuration	Full Metal Shell
Ground Feature Type	Grounding Indents
Connector & Housing Type	Plug
Connector System	Board-to-Board
Connector Shell Size	1
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	9
Number of Rows	2
PCB Mount Orientation	Vertical
Body Features	
Insert Material	Thermoplastic

# **Contact Features**

Connector Profile

Shell Plating Material

Primary Product Color

30 uin
5 5 pm.

Tin

Black

Standard



Contact Mating Area Plating Material	Gold
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Shape & Form	Square
Contact Current Rating (Max)	6 A
Termination Features	
Square Termination Post & Tail Dimension	.63 mm[.025 in]
Termination Post & Tail Length	4.78 mm[.188 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mounting Hole Diameter	3.05 mm[.12 in]
PCB Mount Retention	Without
Mating Retention	Without
Connector Mounting Type	Board Mount
Housing Features	
Shell Material	Carbon Steel
Housing Material	Thermoplastic
Centerline (Pitch)	2.77 mm[.109 in]
Dimensions	
PCB Thickness (Recommended)	2.36 - 3.18 mm[.093125 in]
Row-to-Row Spacing	2.84 mm[.112 in]
Usage Conditions	
Operating Temperature Range	-55 - 105 °C[-67 - 221 °F]
Operation/Application	
Shielded	No
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	17



Packaging Method Tube

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





TE Part # CAT-AM7-253 IDC D-Sub: Receptacle Assembly, Low Profile, Signal, 2.77 mm



TE Part # CAT-AM7-248H8

IDC D-Sub: Receptacle Assembly,
Wire to Wire, Signal, 2.74 mm



Also in the Series | AMPLIMITE HD-20





# Customers Also Bought













MICT,RECPT,38,ASSY,PDNI









# **Documents**

Product Drawings
09 PLUG SP/MS STD

English

**CAD Files** 

3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_5745410-7\_B.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_5745410-7\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5745410-7\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

# Datasheets & Catalog Pages

AMPLIMITE Subminiature D Connectors - Straight Posted Connectors

English

**Product Specifications** 

**Application Specification** 

English