

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C190470	2019/03/21	Vicky	Change Note
C	C220628	2022/05/10	Vicky	△C X4
D	C230087	2023/01/31	Vicky	△D X1


△C CD-XXPMFS-QC8001


XX: No. Of Pin





Recommended Panel Cut-Out













7P



8P



9P

Pin Assignments Front View

△B △C
Note:
* RoHS Compliant
* QC Important dimension
△D * Waterproof rate: IP68, unmated 1m/24h
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper Alloy, Gold plated
* Nut: Thermoplastic, Black
* Gasket: Rubber, Gray
* Use with waterproof cap or dust cap
  Panel thickness max: 3.0mm
* Use without waterproof cap or dust cap
  Panel thickness max: 4.2mm
* Gasket and nut are packed separately in pe bag

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: XLOK, C-5A, FRONT FASTENED M, F, SOLDER, PUSH LOCK △C

SCALE 3:2 | SIZE A4 | SHEET 1 OF 1

REV. D | WC-REV. A.2 | QC: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Vicky	2019-03-21
DWG NO △C CD-XXPMFS-QC8001	CHECKED BY Rita	DATE 2019-03-21
CUSTOMER ALTW	APPROVED BY Max	DATE 2019-03-21

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.