

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON ADVANCE sleeve housing, B10, with stainless steel screw locking (Allen screw), salt-water-resistant aluminum, height 93.7 mm, with 1x M32 thread, straight cable outlet, without surface; conductive seal (EMC properties)

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1413402             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF58                |
| Product key                          | BF7APH              |
| Catalog page                         | Page 603 (C-2-2019) |
| GTIN                                 | 4055626030364       |
| Weight per piece (including packing) | 264 g               |
| Weight per piece (excluding packing) | 262.4 g             |
| Customs tariff number                | 85389099            |
| Country of origin                    | CN                  |

## Technical data

### Notes

|         |                                                  |
|---------|--------------------------------------------------|
| General | For contact inserts HC-B10, BB18, DD42, M, K8/24 |
|---------|--------------------------------------------------|


### Product properties

|                              |                                   |
|------------------------------|-----------------------------------|
| Product type                 | Housing with screw locking        |
| Housing type                 | Sleeve housing                    |
| Product family               | HC-ADV                            |
| Application                  | Offshore/EMC                      |
| Type                         | B10                               |
| No. of cable outlets         | 1                                 |
| Type of the screw connection | 1x M32                            |
| Type                         | Tall design                       |
| Fixing screws                | M6 (screw head: 5 mm Allen screw) |
| Cable outlet                 | straight                          |
| Pg screw connection          | none                              |

### Connection data

|                   |                                                              |
|-------------------|--------------------------------------------------------------|
| Tightening torque | 3 Nm ... 5 Nm (for M6 mounting screws on the sleeve housing) |
|-------------------|--------------------------------------------------------------|

### Dimensions

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width               | 57 mm                                                                                |
| Height              | 93.7 mm                                                                              |
| Length              | 105 mm                                                                               |

#### Installation dimensions

|                               |       |
|-------------------------------|-------|
| Width of the assembly cutout  | 35 mm |
| Length of the assembly cutout | 65 mm |

### Material specifications

|                          |                                         |
|--------------------------|-----------------------------------------|
| Seal material            | NBR, conductive                         |
| Housing material         | Die-cast aluminum, salt water resistant |
| Housing surface material | uncoated                                |
| Locking latch material   | Stainless steel                         |

### Environmental and real-life conditions

#### Ambient conditions

IP66

1413402

<https://www.phoenixcontact.com/us/products/1413402>

|                                 |                          |
|---------------------------------|--------------------------|
| Degree of protection            | IP68 (0.2 bar/24 h)      |
|                                 | IP69 (ISO 20653:2013-02) |
| Enclosure rating (NEMA)         | 4 (UL 50e)               |
|                                 | 4X (UL 50e)              |
|                                 | 12 (UL 50e)              |
| Impact strength                 | IK09                     |
| Ambient temperature (operation) | -40 °C ... 125 °C        |

## Mechanical properties

### Mechanical data


|                              |        |
|------------------------------|--------|
| Type of the screw connection | 1x M32 |
| Locking type                 | Screw  |

## Mounting

|               |                                                                                                                                                                                                            |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Assembly note | In order to guarantee that the protective conductor contact functions even when plugged in at an angle, the two panel-mount flanges must have sufficient electrical contact with the metal mounting panel. |
| Fixing screws | M6 (screw head: 5 mm Allen screw)                                                                                                                                                                          |


## Drawings

Dimensional drawing



Dimensional drawing

Dimensional drawing



Mounting cutout

1) when M4 screws are used

2) when self-tapping Torx® screws are used (Torx® 20, M4)

1413402

<https://www.phoenixcontact.com/us/products/1413402>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1413402>



**DNV**  
Approval ID: TAE000037S



**cUL Recognized**  
Approval ID: E255026



**UL Recognized**  
Approval ID: E255026



**EAC**  
Approval ID: RU C-DE.AI30.B.01102



**EAC**  
Approval ID: RU C-DE.BL08.B.00511

**cULus Recognized**

1413402

<https://www.phoenixcontact.com/us/products/1413402>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440202 |
| ECLASS-12.0 | 27440202 |
| ECLASS-13.0 | 27440202 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000437 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## Accessories

### HC-B-AF - Panel-mount flange

1686533

<https://www.phoenixcontact.com/us/products/1686533>




Panel-mount flange for HEAVYCON ADVANCE housing

---

### HC-B-AF-SET - Panel-mount flange

1604638

<https://www.phoenixcontact.com/us/products/1604638>



Panel-mount flange for HEAVYCON ADVANCE housing, set consisting of:  
2 panel-mount flanges with 4 self-tapping screws (M4, Torx<sup>®</sup>) and 4 fan-type washers

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## HC-B 10-TMS-SD-IP50 - Protective cover

1690749

<https://www.phoenixcontact.com/us/products/1690749>



Protective cover B10, with clip locking, protective cover material: PA, height: 31.2 mm, seal: no, with lanyard

---

## HC-B 10-TMS-SD-IP66 - Protective cover

1411504

<https://www.phoenixcontact.com/us/products/1411504>



HEAVYCON ADVANCE, IP66, B10 protective cover for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet: 3 mm

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## G-INS-M32-M68N-PNES-GY - Cable gland

1411127

<https://www.phoenixcontact.com/us/products/1411127>



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver-grey RAL 7001

---

## G-INS-M32-M68N-NNES-S - Cable gland

1411166

<https://www.phoenixcontact.com/us/products/1411166>



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## HC-M-KV-M32(19-27) - Cable gland

1646010

<https://www.phoenixcontact.com/us/products/1646010>



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32

---

## US-EMLP-HA (20X9) - Plastic label

0830989

<https://www.phoenixcontact.com/us/products/0830989>



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## US-EMLP-HA (20X9) CUS - Plastic label

0830995

<https://www.phoenixcontact.com/us/products/0830995>

Plastic label, Card, white, labeled, can be labeled with: THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70



---

## WP-G HF IP66 M32 BK - Screw connection

3240900

<https://www.phoenixcontact.com/us/products/3240900>

Cable gland, metric thread, IP66 protection, straight



# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## WP-G HF IP69K M32 BK - Screw connection

3240886

<https://www.phoenixcontact.com/us/products/3240886>

Cable gland, metric thread, IP68/69k protection, straight



---

## WP-GA HF IP66 M32 BK - Screw connection

3240928

<https://www.phoenixcontact.com/us/products/3240928>

Cable gland, metric thread, IP66 protection, angled



# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing

1413402

<https://www.phoenixcontact.com/us/products/1413402>



## WP-GA HF IP69K M32 BK - Screw connection

3240914

<https://www.phoenixcontact.com/us/products/3240914>

Cable gland, metric thread, IP68/69k protection, angled



---

## WP-GR HF IP66 M32 BK - Screw connection

3240956

<https://www.phoenixcontact.com/us/products/3240956>

Cable gland, metric thread, IP66 protection, with strain relief



# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## WP-GR HF IP69K M32 BK - Screw connection

3240942

<https://www.phoenixcontact.com/us/products/3240942>



Cable gland, metric thread, IP68/69k protection, with strain relief

---

## WP-G PP HF M32 - Screw connection

3241000

<https://www.phoenixcontact.com/us/products/3241000>



Cable gland made from PP with metric thread, IP65 protection

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## WP-GT PP HF M32 - Screw connection

3241014

<https://www.phoenixcontact.com/us/products/3241014>



Cable gland made from PP with metric thread, rotatable, IP54 protection

---

## WP-G BRASS IP40 M32 - Screw connection

3241049

<https://www.phoenixcontact.com/us/products/3241049>



Cable gland made from brass with metric thread, IP40 protection

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## WP-GT BRASS M32 - Screw connection

3241035

<https://www.phoenixcontact.com/us/products/3241035>



Cable gland made from brass with metric thread, rotatable, IP40 protection

---

## WP-G BRASS IP65 M32 - Screw connection

3241063

<https://www.phoenixcontact.com/us/products/3241063>



Cable gland made from brass with metric thread, IP65 protection

# HC-ADV-B10-HHWH-1TTM32-EMC-AL - Housing



1413402

<https://www.phoenixcontact.com/us/products/1413402>

## SF-BIT-HEXB 5-89 - Screw insert

1208911

<https://www.phoenixcontact.com/us/products/1208911>



Screw bit, hexagonal with ball head, E6.3-1/4" drive, size: Hex 5 x 89 mm, hardened, suitable for holder according to DIN 3126-F 6.3/ISO 1173

---

## SF-M BH - Screwdriver

1212070

<https://www.phoenixcontact.com/us/products/1212070>



Bit screwdriver, with 1/4" quick-action chuck, handle length 119 mm, 2-component handle, with non-slip grip, suitable for bits according to DIN 3126-C 6.3 and E 6.3/ISO 1173, magnetic

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)