3-643230-0 ✔ ACTIVE

MATE-N-LOK | Universal MATE-N-LOK

TE Internal #: 3-643230-0

Rectangular Power Connectors, Header, Receptacle, Wire-to-Board, 4 Position, 6.35 mm [.25 in] Centerline, Printed Circuit Board, Universal MATE-N-LOK

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **4**

Centerline (Pitch): **6.35 mm [.25 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	4
PCB Mount Orientation	Right Angle
Number of Power Positions	4
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VAC

Contact Features

Multiple Contact Types	Without

PCB Contact Termination Area Plating Material Thickness	2.54 µm[100 µin]
Contact Layout	Inline
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	12 A
Contact Retention Within Housing	Without
Contact Type	Socket
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]

Termination Features

Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	With
PCB Mount Retention Type	Mounting Hole
Mating Retention Type	Positive Lock
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	6.35 mm[.25 in]
Housing Color	Natural
Housing Material	Nylon

Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]

Usage Conditions

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]

Operation/Application

Circuit Application	Power

Industry Standards

CSA Rating	Certified, LR 7189
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	140
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 641776-1
04P UMNL STR/REL



TE Part # 641776-2
04P UMNL STR/REL



TE Part # 770019-1
04P UMNLII IN-LNE PLUG HSG KIT

TE Part # 1-350589-0
STR/REL CLAMP NATL

TE Part # 350811-1
STR/REL CLAMP

TE Part # 350779-1
04P UMNL PLUG HSG



TE Part # 641775-1
04P UMNL STR/REL & INSRT NATL

TE Part # 1586845-1
04P UMNL CAP HSG NATL, GW

TE Part # 641968-3
04P UMNL PIN HDR ASSY POL 94VO

TE Part # 794273-1
04P UMNL INTERFACE SEAL

TE Part # 794274-1
04P UMNL WIRE SEAL

TE Part # 2-480703-0
04P UMNL CAP HSG NATL

TE Part # 794707-1
04P UMNL CAP HSG,BLACK

TE Part # 641775-2
04P UMNL STR/REL NATL

TE Part # 926305-6
UNML4WAY CAP



TE Part # 350848-4
04P UMNL PLUG TEST ASSY 94VO

TE Part # 641968-4
4P UMNL PIN HDR POL VO, AU, LF

TE Part # 926305-1
4P UNIV M-N-L CAP

Also in the Series | Universal MATE-N-LOK

Circular Power Connectors(2)

Connector Caps & Covers(34)

Connector Contacts(209)

Connector Hardware(12)

Connector Seals & Cavity Plugs(27)

Connector Strain Relief(7)

Insertion & Extraction Tools(4)

Rectangular Connector Housings(1)

Rectangular Power Connectors(671)

Standard Circular Connectors(1)

Customers Also Bought

TE Part # 2102353-2
CeeLok FAS-T, Plug Kit, ZnNi

TE Part # 350428-1
02P UMNL PIN HDR ASSY NATL

TE Part # 170780-1
P.G RING UL.CSA(22-18)



TE Part # 280609-1
2P MOD 1 SHROUDED HEADER, ST, TIN PLTD

TE Part # 1-794612-1
PIN CONT 20-24 15 GOLD L/P



TE Part # 234062-002
2524E0114-9



TE Part # 8-2176406-5
3560 3K3 1%



TE Part # 104074-2
05 SYSTEM 50 HDR SRRA SHRD



TE Part # 6-1416200-7
V23061-D2007-A801

TE Part # 0600-00048
ANT,900MHz, 2dBi

Documents

Product Drawings

04P UMNL HDR ASSY R/A 94VO LF

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-643230-0_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-643230-0_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-643230-0_J.3d_stp.zip

English

Customer View Model

ENG_CVM_3-643230-0_E.3d_igs.zip

English

Customer View Model

ENG_CVM_3-643230-0_E.3d_stp.zip

English

Customer View Model

ENG_CVM_3-643230-0_E.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY

English

Product Specifications

Application Specification

English