

Power Relay F

TE Internal #: 7-1393304-1

Mini Relays, 12VDC Coil Voltage Rating, 30 - 50A Contact Current

Class, Contact Arrangement 1 Form U (NO-DM), Rp 1200Ω , Socket,

Power Relay F

View on TE.com >



Relays & Contactors > Relays > Automotive Relays > Automotive Plug-In Relays > Mini Relays



Coil Voltage Rating: 12 VDC

Contact Current Class: 30 - 50 A

Contact Arrangement: 1 Form U (NO-DM)

Coil Special Features: Rp 1200Ω Product Mount Type: Socket

Features

Configuration Features

Contact Arrangement	1 Form U (NO-DM)
Coil Special Features	Rp 1200Ω
Electrical Characteristics	
Contact Limiting Short-Time Current	240 A
Contact Limiting Continuous Current	32 A
Current Rating (85°C)	40 A
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Limiting Making Current	100 A
Insulation Initial Dielectric Between Contacts & Coil	500 Vrms
Contact Limiting Breaking Current	40 A
Contact Voltage Rating	12 VDC
Contact Switching Load (Min)	1000mA @ 5VDC
Coil Power Rating DC	1600 mW
Coil Voltage Rating	12 VDC
Coil Resistance	90 Ω
Body Features	

35 g[1.2 oz]

Product Weight

Contact Features



Contact Material	Silver Alloy
Termination Features	
Relay Connection Type	Plug-In
Terminal Configuration	Quick Connect Terminals
Mechanical Attachment	
Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Socket
Dimensions	
Product Width	25.9 mm[1.02 in]
Product Length	25.9 mm[1.02 in]
Product Height	24.9 mm[.98 in]
Usage Conditions	
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Coil Magnetic System	Monostable, DC
Coil Magnetic System Other	Monostable, DC
	Monostable, DC 25 - 30 mm
Other	
Other Length Class (Mechanical)	25 - 30 mm
Other Length Class (Mechanical) Environmental Ambient Temperature Class	25 - 30 mm 105 - 125 °C
Other Length Class (Mechanical) Environmental Ambient Temperature Class Insulation Initial Dielectric Between Coil & Contact Class	25 - 30 mm 105 - 125 °C 0 - 500 V

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC



Not applicable for solder process capability

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC
	Free

Product Compliance Disclaimer


Solder Process Capability

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Power Relay F






Customers Also Bought






TE Part # DTM04-12PA-L012 REC, 12P, GRY, N, FLANGE, A



TE Part # 971078-000 382A023-25/225-0



TE Part # 368049-1 E-J MK-II(+) 16P PLUG DBL



TE Part # 650076-000 D-436-38



TE Part # 1393315-9 V23132B2002A200=HCR









Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-1393304-1_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_7-1393304-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-1393304-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

Power Relay F4, Mini ISO, Plug-In

English

Mini Relays, 12VDC Coil Voltage Rating, 30 - 50A Contact Current Class, Contact Arrangement 1 Form U (NO-DM), Rp 1200Ω , Socket, Power Relay F



Product Specifications

Definitions General Purpose Relays

English