



: 458450002

: 45845

Product Category : Card Edge Connectors

Product Description : 2.50mm Pitch EXTreme PowerEdge Signal Connector, Double Sided, 3 Segments, 8 Signal Contacts per Segment, Press-Fit
: Active

458450002_sd.pdf
PK-45714-001-001.pdf

3D
3D 458450002_stp.zip

PS-45719-001-001.pdf
TS-45844-001-001.pdf

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

	Card Edge Connectors
	45845
	2.50mm Pitch EXTreme PowerEdge Signal Connector, Double Sided, 3 Segments, 8 Signal Contacts per Segment, Press-Fit
	Edgecard to PCB
	Edge Card Connectors
	EXTreme PowerEdge
UPC	822348847709

Agency

CSA	LR19980
-----	---------

-	3.0A
	Unrated
30.0A	
-	250V

/

	1-64 Circuits
	24
	24
-	
	250
	1.57mm
	Vertical (Top Entry)
	94V-0

	N/A
-	Phosphor Bronze
-	
-	Tin
-	High Temperature Thermoplastic
	4.849/g
	Tray
	4.50mm
PCB -	2.40mm
-	2.50mm
	0.762µm
	3.810µm
(p)ower-(s)ignal	24s - 0p
	-40° to +105°C
	Through Hole - Compliant Pin

	N/A
--	-----

/

	1.58mm Double Sided Card Edge