

| APPLICABLE STANDARD                                                                                                                                                                 |                             |                                                                                               |                                                                                              |                                |          |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|--------------------------------|----------|
| RATING                                                                                                                                                                              | OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C <sup>(1)</sup>                                                                | STORAGE TEMPERATURE RANGE                                                                    | -10 °C TO 60 °C <sup>(2)</sup> |          |
|                                                                                                                                                                                     | VOLTAGE                     | 100 V AC                                                                                      | OPERATING HUMIDITY RANGE                                                                     | 40 % TO 80 %                   |          |
|                                                                                                                                                                                     | CURRENT                     | 0.5 A                                                                                         | STORAGE HUMIDITY RANGE                                                                       | 40 % TO 70 % <sup>(2)</sup>    |          |
| SPECIFICATIONS                                                                                                                                                                      |                             |                                                                                               |                                                                                              |                                |          |
| ITEM                                                                                                                                                                                |                             | TEST METHOD                                                                                   | REQUIREMENTS                                                                                 | QT                             | AT       |
| CONSTRUCTION                                                                                                                                                                        |                             |                                                                                               |                                                                                              |                                |          |
| GENERAL EXAMINATION                                                                                                                                                                 |                             | VISUALLY AND BY MEASURING INSTRUMENT.                                                         | ACCORDING TO DRAWING.                                                                        | x                              | x        |
| MARKING                                                                                                                                                                             |                             | CONFIRMED VISUALLY.                                                                           |                                                                                              | x                              | x        |
| ELECTRIC CHARACTERISTICS                                                                                                                                                            |                             |                                                                                               |                                                                                              |                                |          |
| CONTACT RESISTANCE                                                                                                                                                                  |                             | 100 mA (DC OR 1000 Hz).                                                                       | 40 mΩ MAX.                                                                                   | x                              | —        |
| CONTACT RESISTANCE MILLIVOLT LEVEL METHOD                                                                                                                                           |                             | 20 mV MAX, 1 mA(DC OR 1000Hz)                                                                 | 50 mΩ MAX.                                                                                   | x                              | —        |
| INSULATION RESISTANCE                                                                                                                                                               |                             | 250 V DC                                                                                      | 100 MΩ MIN.                                                                                  | x                              | —        |
| VOLTAGE PROOF                                                                                                                                                                       |                             | 300 V AC FOR 1 min.                                                                           | NO FLASHOVER OR BREAKDOWN.                                                                   | x                              | —        |
| MECHANICAL CHARACTERISTICS                                                                                                                                                          |                             |                                                                                               |                                                                                              |                                |          |
| INSERTION AND WITHDRAWAL FORCES                                                                                                                                                     |                             | MEASURED BY APPLICABLE CONNECTOR.                                                             | INSERTION FORCE : 88.2 N MAX.<br>WITHDRAWAL FORCE : 9.8 N MIN.                               | x                              | —        |
| MECHANICAL OPERATION                                                                                                                                                                |                             | 100 TIMES INSERTIONS AND EXTRACTIONS.                                                         | ① CONTACT RESISTANCE: 50 mΩ MAX.<br>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.               | x                              | —        |
| VIBRATION                                                                                                                                                                           |                             | FREQUENCY 10 TO 55 Hz,<br>AMPLITUDE : 1.5 mm,<br>AT 2 h FOR 3 DIRECTIONS.                     | ① NO ELECTRICAL DISCONTINUITY OF 1 μs.<br>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.         | x                              | —        |
| SHOCK                                                                                                                                                                               |                             | 490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms<br>AT 3 TIMES FOR 3 DIRECTIONS.                |                                                                                              | x                              | —        |
| ENVIRONMENTAL CHARACTERISTICS                                                                                                                                                       |                             |                                                                                               |                                                                                              |                                |          |
| DAMP HEAT (STEADY STATE)                                                                                                                                                            |                             | EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.                                                          | ① CONTACT RESISTANCE: 50 mΩ MAX.<br>② INSULATION RESISTANCE: 100 MΩ MIN.                     | x                              | —        |
| RAPID CHANGE OF TEMPERATURE                                                                                                                                                         |                             | TEMPERATURE -55→+15~+35→+85→+15~+35 °C<br>TIME 30 → MAX 5 → 30 → MAX 5 min<br>UNDER 5 CYCLES. | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.                                                   | x                              | —        |
| CORROSION SALT MIST                                                                                                                                                                 |                             | EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.                                                     | ① CONTACT RESISTANCE: 50 mΩ MAX.<br>② NO HEAVY CORROSION.                                    | x                              | —        |
| HYDROGEN SULPHIDE                                                                                                                                                                   |                             | EXPOSED IN 3 PPM FOR 96 h.<br>(TEST STANDARD: JEIDA 38)                                       |                                                                                              | x                              | —        |
| RESISTANCE TO SOLDERING HEAT                                                                                                                                                        |                             | 1) REFLOW SOLDERING : 250 °C MAX,<br>: 220 °C MIN,<br>FOR 60 s                                | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.                              | x                              | —        |
|                                                                                                                                                                                     |                             | 2) SOLDERING IRONS : 360 °C,<br>FOR 5 s                                                       |                                                                                              | x                              | —        |
| SOLDERABILITY                                                                                                                                                                       |                             | SOLDERED AT SOLDER TEMPERATURE, 240±3 °C,<br>FOR IMMERSION DURATION, 3 s.                     | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | x                              | —        |
|                                                                                                                                                                                     |                             |                                                                                               |                                                                                              |                                |          |
|                                                                                                                                                                                     | COUNT                       | DESCRIPTION OF REVISIONS                                                                      | DESIGNED                                                                                     | CHECKED                        | DATE     |
| △                                                                                                                                                                                   |                             |                                                                                               |                                                                                              |                                |          |
| REMARK <sup>(1)</sup> TEMPERATURE RISE INCLUDED WHEN ENERGIZED.<br><sup>(2)</sup> THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. |                             |                                                                                               | APPROVED                                                                                     | HS. OKAWA                      | 08.06.16 |
|                                                                                                                                                                                     |                             |                                                                                               | CHECKED                                                                                      | HT. YAMAGUCHI                  | 08.06.16 |
|                                                                                                                                                                                     |                             |                                                                                               | DESIGNED                                                                                     | TS. MIYAKI                     | 08.06.16 |
|                                                                                                                                                                                     |                             |                                                                                               | DRAWN                                                                                        | TS. MIYAKI                     | 08.06.16 |
| Unless otherwise specified, refer to MIL-STD-1344.                                                                                                                                  |                             |                                                                                               |                                                                                              |                                |          |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test                                                                                                                      |                             |                                                                                               | DRAWING NO.                                                                                  | ELC4-071337-25                 |          |
| <b>HRS</b>                                                                                                                                                                          | SPECIFICATION SHEET         |                                                                                               | PART NO.                                                                                     | FX6A-100S-0.8SV (71)           |          |
|                                                                                                                                                                                     | HIROSE ELECTRIC CO., LTD.   |                                                                                               | CODE NO.                                                                                     | CL576-0308-6-71                | △ 1/1    |