

2981839

<https://www.phoenixcontact.com/us/products/2981839>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Safe coupling relay with force-guided contacts, 3 N/O contacts, 3 N/C contacts, plug-in screw terminal block, width: 22.5 mm

Your advantages

- Up to Cat. 1/PL c in accordance with EN ISO 13849-1, SIL 1 in accordance with IEC 61508
- Safe readback due to force-guided signal contact in accordance with EN 50205
- Easy proof test according to IEC 61508 thanks to integrated signal contact
- 1 or 2-channel control
- 3 enabling current paths, 3 confirmation current paths

Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2981839             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | DN01                |
| Product key                          | DNA162              |
| Catalog page                         | Page 246 (C-6-2019) |
| GTIN                                 | 4046356138604       |
| Weight per piece (including packing) | 153.7 g             |
| Weight per piece (excluding packing) | 126.9 g             |
| Customs tariff number                | 85364900            |
| Country of origin                    | DE                  |

# PSR-SCP- 24UC/URM/3X1/3X2 - Coupling relay



2981839

<https://www.phoenixcontact.com/us/products/2981839>

## Technical data

### Notes

|                     |                         |
|---------------------|-------------------------|
| Note on application | Only for industrial use |
|---------------------|-------------------------|

### Product properties

|                         |                                                                                      |
|-------------------------|--------------------------------------------------------------------------------------|
| Product type            | Coupling relay                                                                       |
| Product family          | PSRclassic                                                                           |
| Application             | Safe switch off                                                                      |
|                         | High demand                                                                          |
|                         | Low demand                                                                           |
| Mechanical service life | 10x 10 <sup>6</sup> cycles                                                           |
| Relay type              | Electromechanical relay with force-guided contacts in accordance with IEC/EN 61810-3 |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 06 |
|------------------|----|

### Times

|              |                   |
|--------------|-------------------|
| Restart time | < 1 s (Boot time) |
|--------------|-------------------|

### Electrical properties

|                                                 |                                                                                                                                                                                                                              |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum power dissipation for nominal condition | 6.11 W (at $U_B = 26.4$ V DC, $U_S = 24$ V, $I_S = 45$ mA, $n = 1$ , $I_L^2 = 48$ A <sup>2</sup> , $R_{\text{contact}} = 0.1 \Omega$  ) |
| Nominal operating mode                          | 100% operating factor                                                                                                                                                                                                        |

### Air clearances and creepage distances between the power circuits

|                                |                                                                                                                            |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Rated insulation voltage       | 250 V                                                                                                                      |
|                                | 250 V                                                                                                                      |
| Rated surge voltage/insulation | 4 kV / Basic isolation, (safe isolation, reinforced insulation and 6 kV between input circuit and enabling current paths.) |

### Supply

|                                            |                               |
|--------------------------------------------|-------------------------------|
| Rated control circuit supply voltage $U_S$ | 20.4 V AC/DC ... 26.4 V AC/DC |
|--------------------------------------------|-------------------------------|

### Input data

#### General

|                                            |                                                  |
|--------------------------------------------|--------------------------------------------------|
| Rated control circuit supply voltage $U_S$ | 24 V AC/DC -15 % / +10 %                         |
| Power consumption at $U_S$                 | typ. 1.08 W                                      |
| Rated control supply current $I_S$         | typ. 45 mA                                       |
| Input voltage range                        | 20.4 V AC/DC ... 26.4 V AC/DC                    |
| Inrush current                             | typ. 350 mA DC ( $\Delta t < 1 \mu s$ at $U_S$ ) |
|                                            | typ. 350 mA AC ( $\Delta t = 2$ ms at $U_S$ )    |
| Typ. starting time with $U_S$              | typ. 15 ms (when controlled via A1)              |
| Typical release time                       | typ. 15 ms (when controlled via A1)              |
| Recovery time                              | < 500 ms                                         |

# PSR-SCP- 24UC/URM/3X1/3X2 - Coupling relay



2981839

<https://www.phoenixcontact.com/us/products/2981839>

|                             |                                    |
|-----------------------------|------------------------------------|
| Maximum switching frequency | 0.5 Hz                             |
| Protective circuit          | Surge protection; Suppressor diode |
| Operating voltage display   | 1 x green LED                      |

## Output data

|                                                     |                                                      |
|-----------------------------------------------------|------------------------------------------------------|
| Contact switching type                              | 3 enabling current paths                             |
|                                                     | 3 confirmation current paths                         |
| Contact material                                    | AgSnO <sub>2</sub>                                   |
| Maximum switching voltage                           | 230 V AC/DC (Observe the load curve)                 |
| Minimum switching voltage                           | 5 V AC/DC                                            |
| Limiting continuous current                         | 6 A (N/O contact)                                    |
|                                                     | 6 A (N/C contact)                                    |
| Maximum inrush current                              | 8 A                                                  |
| Inrush current, minimum                             | 10 mA                                                |
| Sq. Total current                                   | 48 A <sup>2</sup>                                    |
| Interrupting rating (ohmic load) max.               | For additional values, see load curve                |
| Maximum interrupting rating (inductive load)        | 48 W (N/O contact, 24 V DC, $\tau = 40$ ms)          |
|                                                     | 40 W (N/O contact, 48 V DC, $\tau = 40$ ms)          |
|                                                     | 36 W (N/O contact, 60 V DC, $\tau = 40$ ms)          |
|                                                     | 35 W (N/O contact, 110 V DC, $\tau = 40$ ms)         |
|                                                     | 33 W (N/O contact, 220 V DC, $\tau = 40$ ms)         |
| Switching capacity                                  | min. 50 mW                                           |
| Switching capacity in accordance with IEC 60947-5-1 | 5 A (24 V (DC13))                                    |
|                                                     | 5 A (230 V (AC 15))                                  |
| Output fuse                                         | 10 A gL/gG (N/O contact)                             |
|                                                     | 4 A gL/gG (N/O contact, for low-demand applications) |
|                                                     | 6 A gL/gG (N/C contact)                              |

## Relay

|                   |   |
|-------------------|---|
| Number of outputs | 3 |
|-------------------|---|

## Connection data

### Connection technology

|           |     |
|-----------|-----|
| pluggable | yes |
|-----------|-----|

### Conductor connection

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Connection method                | Screw connection                            |
| Conductor cross section rigid    | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross section flexible | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross-section AWG      | 24 ... 12                                   |
| Stripping length                 | 7 mm                                        |
| Screw thread                     | M3                                          |
| Tightening torque                | 0.6 Nm                                      |

## Dimensions

# PSR-SCP- 24UC/URM/3X1/3X2 - Coupling relay



2981839

<https://www.phoenixcontact.com/us/products/2981839>

|        |          |
|--------|----------|
| Width  | 22.5 mm  |
| Height | 114.5 mm |
| Depth  | 99 mm    |

## Material specifications

|                  |                   |
|------------------|-------------------|
| Color (Housing)  | yellow (RAL 1018) |
| Housing material | Polyamide         |

## Characteristics

### Safety data

|               |   |
|---------------|---|
| Stop category | 0 |
|---------------|---|

### Safety data: EN ISO 13849

|                        |   |
|------------------------|---|
| Category               | 1 |
| Performance level (PL) | c |

### Safety data: IEC 61508 - High demand

|                              |   |
|------------------------------|---|
| Safety Integrity Level (SIL) | 1 |
|------------------------------|---|

### Safety data: IEC 61508 - Low demand

|                              |   |
|------------------------------|---|
| Safety Integrity Level (SIL) | 1 |
|------------------------------|---|

### Safety data

|                              |   |
|------------------------------|---|
| Safety Integrity Level (SIL) | 1 |
|------------------------------|---|

## Environmental and real-life conditions

### Ambient conditions

|                                                |                                                                                                                   |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Degree of protection                           | IP20                                                                                                              |
| Min. degree of protection of inst. location    | IP54                                                                                                              |
| Ambient temperature (operation)                | -20 °C ... 55 °C                                                                                                  |
| Ambient temperature (storage/transport)        | -40 °C ... 70 °C                                                                                                  |
| Maximum altitude                               | max. 2000 m (Above sea level)                                                                                     |
| Max. permissible humidity (storage/transport)  | 75 % (on average, 85% infrequently, non-condensing)                                                               |
| Max. permissible relative humidity (operation) | 75 % (on average, 85% infrequently, non-condensing)                                                               |
| Shock                                          | 15g (In the event of stress caused by shock, contact reactions are possible for up to 2 ms.)                      |
| Vibration (operation)                          | 10 Hz ... 150 Hz, 2g (In the event of stress caused by vibration, contact reactions are possible for up to 1 ms.) |

## Approvals

### CE

|             |              |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

## Standards and regulations

Air clearances and creepage distances between the power circuits

# PSR-SCP- 24UC/URM/3X1/3X2 - Coupling relay



2981839

<https://www.phoenixcontact.com/us/products/2981839>

|                       |              |
|-----------------------|--------------|
| Standards/regulations | DIN EN 50178 |
|-----------------------|--------------|

## Mounting

|                   |                        |
|-------------------|------------------------|
| Mounting type     | DIN rail mounting      |
| Mounting position | vertical or horizontal |

PSR-SCP- 24UC/URM/3X1/3X2 - Coupling relay




2981839

<https://www.phoenixcontact.com/us/products/2981839>


Drawings

Application drawing



Reliable signal exchange between two systems with confirmation function.

Block diagram



Block diagram

# PSR-SCP- 24UC/URM/3X1/3X2 - Coupling relay



2981839

<https://www.phoenixcontact.com/us/products/2981839>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2981839>



**EAC**  
Approval ID: TR\_TS\_D\_00573\_c



**UL Listed**  
Approval ID: FILE E 140324



**cUL Listed**  
Approval ID: FILE E 140324



**Functional Safety**  
Approval ID: 44-780-15124312



**Functional Safety**  
Approval ID: 44-205-15124312

**cULus Listed**

# PSR-SCP- 24UC/URM/3X1/3X2 - Coupling relay



2981839

<https://www.phoenixcontact.com/us/products/2981839>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27371819 |
| ECLASS-13.0 | 27371819 |
| ECLASS-12.0 | 27371819 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001449 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39122200 |
|-------------|----------|

Environmental product compliance

|                                         |                                                                                                                                                                                                                                   |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS                                 |                                                                                                                                                                                                                                   |
| Fulfills EU RoHS substance requirements | Yes                                                                                                                                                                                                                               |
| Exemption                               | 7(a)                                                                                                                                                                                                                              |
| China RoHS                              |                                                                                                                                                                                                                                   |
| Environment friendly use period (EFUP)  | EFUP-50                                                                                                                                                                                                                           |
|                                         | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC                           |                                                                                                                                                                                                                                   |
| REACH candidate substance (CAS No.)     | Hexahydromethylphthalic anhydride(CAS: n/a)                                                                                                                                                                                       |
|                                         | Lead(CAS: 7439-92-1)                                                                                                                                                                                                              |
| SCIP                                    | 5041cc60-3446-4624-b4dc-2d798efd9a11                                                                                                                                                                                              |

# PSR-SCP- 24UC/URM/3X1/3X2 - Coupling relay



2981839

<https://www.phoenixcontact.com/us/products/2981839>

## Accessories

### CRIMPFOX 6 - Crimping pliers

1212034

<https://www.phoenixcontact.com/us/products/1212034>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm<sup>2</sup> ... 6.0 mm<sup>2</sup>, lateral entry, trapezoidal crimp

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)