# Data sheet

## 3624.2 ZTRK 2,5/3A/ZS 150 BG



Fuse-disconnect terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

## Business data

| | |
|---|---|
| Article number | 3624.2 |
| Article name | ZTRK 2,5/3A/ZS 150 BG |
| GTIN (EAN) | 4044211059880 |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 18 g |
| Weight per piece (including packaging) | 19 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |
| Product description | Fuse-disconnect terminal |

# Data sheet

## 3624.2 ZTRK 2,5/3A/ZS 150 BG

## Technical data

### Dimensions

| | |
|---|---|
| Length | 80.2 mm |
| Width | 5.1 mm |
| Height TS 35/7.5 | 78.7 mm |

### Ratings

| | |
|---|---|
| Rated voltage (determined by the illuminated display and fuse being used) | 150 V |
| Rated current (as fuse-disconnect terminal) | 18 A |
| Rated cross-section | 2.5 mm² |
| Rated impulse voltage | 6 kV |
| Overvoltage category | III |
| Contamination degree | 3 |

### Connection data

| | |
|---|---|
| Connection principle | Tension-spring connection |
| Connection position | Diagonal |
| Connections | 3 |
| Number of terminals per level | 3 |
| Number of levels | 1 |
| Wire cross-section single-core (rigid) / stranded, min. | 0.5 mm² |
| Wire cross-section single core (rigid)/stranded, max. | 4 mm² |
| Wire cross-section stranded, min. | 0.5 mm² |
| Wire cross-section stranded, max. | 4 mm² |
| Wire cross-section stranded with wire-end ferrules, min. | 0.5 mm² |
| Wire cross-section stranded with wire-end ferrules, max. | 2.5 mm² |
| Wire cross-section AWG, min. | 12 |
| Wire cross-section AWG, max. | 20 |
| Stripping length | 10 mm |

# Data sheet

## 3624.2 ZTRK 2,5/3A/ZS 150 BG

## Technical data

### Further technical data

| | |
|---|---|
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-0 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 120 °C |
| Mounting type | Mounting rail TS 35/7,5 |
| Fuse size | 5 x 20 mm |
| Gauge plug acc. to EN 60 947-1 | A3 |
| Number of cross-connection channels | 1 |
| End plate required | ✓ |
| Number of test pick-off options | 2 |
| Voltage illuminated display | 60-150 V |
| Cross-current via illuminated display | 5 mA |
| Power loss in singular arrangement - overload and short-circuit protection, max. | 2,5 / 6,3 W / A |
| Power loss in compound arrangement - overload and short-circuit protection, max. | 1,6 / 6,3 W / A |
| Power loss in singular arrangement - only short-circuit protection, max. | 4 / 6,3 W / A |
| Power loss in compound arrangement - only short-circuit protection, max. | 2,5 / 6,3 W / A |
| Version of fuse holder | Pluggable |
| Type of display element (defect display) | LED |
| Version of fuse cartridge | G fuse 5 x 20 |
| Supply voltage (defect display), min. | 60 |
| Supply voltage (defect display), max. | 150 |
| Type of voltage (defect display) | AC/DC |

### Print

| | |
|---|---|
| Colour | Beige |

### Environmental Product Compliance

| | |
|---|---|
| REACH Conform | Yes |
| REACH Candidate Substance Note | No |

## Approvals

### CSA approval

| | |
|---|---|
| CSA approval | C22.2 No 158 |
| CSA approval granted | yes |
| CSA Usegroup B: rated voltage | 300 V |
| CSA Usegroup B: rated current | 10 A |
| CSA Usegroup C: rated voltage | 300 V |
| CSA Usegroup C: rated current | 10 A |
| CSA wire cross-section AWG, min. | 20 |
| CSA wire cross-section AWG, max. | 12 |
| CSA stripping length | 10 mm |

### CSAus approval

| | |
|---|---|
| CSAus approval | UL 1059 |
| CSAus approval granted | yes |
| CSAus Usegroup B: rated voltage | 300 V |
| CSAus Usegroup B: rated current | 10 A |
| CSAus Usegroup C: rated voltage | 300 V |
| CSAus Usegroup C: rated current | 10 A |
| CSAus wire cross-section AWG, min. | 20 |
| CSAus wire cross-section AWG, max. | 12 |
| CSAus stripping length | 10 mm |

## Approvals

### KEMA KEUR approval


| | |
|---|---|
| KEMA KEUR approval | EN 60947-7-1:2009, EN 60947-7-3:2009 |
| KEMA KEUR approval granted | yes |
| KEMA rated voltage | 150 V |
| KEMA rated current | 6,3 A |
| KEMA rated impulse voltage (fuse holder withoutelectrical components) | 6 (4) kV |
| KEMA wire cross-section single core (rigid), min. | 0.5 mm² |
| KEMA wire cross-section single-core (rigid), max. | 4 mm² |
| KEMA wire cross-section stranded, min. | 0.5 mm² |
| KEMA wire cross-section stranded, max. | 4 mm² |
| KEMA power loss in singular arrangement - overloadand short-circuit protection, max. | 2,5 / 6,3 W / A |
| KEMA power loss in compound arrangement -overload and short-circuit protection, max. | 1,6 / 6,3 W / A |
| KEMA power loss in singular arrangement - only short-circuit protection, max. | 4 / 6,3 W / A |
| KEMA power loss in compound arrangement - only short-circuit protection, max. | 2,5 / 6,3 W / A |


# Data sheet


## 3624.2 ZTRK 2,5/3A/ZS 150 BG

### Media









## Accessories

### End plate




End plate, Width: 1.5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3797.2 | ZAPT 2,5/3A BG | 4044211061319 | 20 |

### Actuating tool

### End stop



End stop, Mounting type: Mounting rail TS 35/7.5 and TS 35/15, Width: 6 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3748.2 | ZES 35 BG | 4044211060572 | 50 |

### Test adapter



Test adapter, Pitch size: 5.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3740.2 | ZTA 2,5 BG | 4044211060497 | 10 ST |

### Insulated cross-connector



Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 34.6 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3715.8 | ZQI 2,5/7 YE | 4044211060336 | 20 |

# Data sheet

## 3624.2 ZTRK 2,5/3A/ZS 150 BG

### Insulated cross-connector



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 9.1 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3710.8 | ZQI 2,5/2 YE | 4044211060282 | 50 |



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 49.9 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3718.8 | ZQI 2,5/10 YE | 4044211060367 | 10 |



Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 14.2 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3711.8 | ZQI 2,5/3 YE | 4044211060299 | 50 |



Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 24.4 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3713.8 | ZQI 2,5/5 YE | 4044211060312 | 20 |



Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 39.7 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3716.8 | ZQI 2,5/8 YE | 4044211060343 | 10 |



Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 19.3 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3712.8 | ZQI 2,5/4 YE | 4044211060305 | 20 |

# Data sheet

## 3624.2 ZTRK 2,5/3A/ZS 150 BG

### Insulated cross-connector



Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 29.5 mm, Rated cross-section: 2.5 mm², Colour: Yellow


| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3714.8 | ZQI 2,5/6 YE | 4044211060329 | 20 |



Insulated cross-connector, No. of poles: 99, Mounting type: Plug in, Width: 500 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3719.8 | ZQI 2,5/0,5 m/99 Pole YE | 4044211060374 | 2 |

### Quick marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 5 mm, Colour: White

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 4600.7 | PMC SB 5/50 WH | 4044211088903 | 500 ST |

### Four-way cover



Cover, Length: 6.7 mm, Width: 20.4 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|---|---|---|---|
| 3706.0 | ZAD 2,5/4/B YE | 4044211060244 | 20 ST |