Pushing Performance
Since 1945

# Han ES 24B PE-CC Male




Image is for illustration purposes only. Please refer to product description.

| | |
|---|---|
| Part number | 09 33 024 2676 |
| Specification | Han ES 24B PE-CC Male |
| HARTING eCatalogue | https://b2b.harting.com/09330242676 |

## Identification

| | |
|---|---|
| Category | Inserts |
| Series | Han® ES |
| Specification | Cage clamp termination for PE connection |

## Version

| | |
|---|---|
| Termination method | Cage-clamp termination |
| Gender | Male |
| Size | 24 B |
| Number of contacts | 24 |
| PE contact | Yes |

## Technical characteristics

| | |
|---|---|
| Conductor cross-section | 0.14 ... 2.5 mm² |
| Conductor cross-section | AWG 26 ... AWG 14 |
| Rated current | 16 A |
| Rated voltage | 500 V |
| Rated impulse voltage | 6 kV |
| Pollution degree | 3 |
| Rated voltage acc. to UL | 600 V |
| Rated voltage acc. to CSA | 600 V |
| Insulation resistance | $>10^{10}$ Ω |
| Contact resistance | ≤3 mΩ |
| Stripping length | 7 ... 9 mm |


HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Pushing Performance
Since 1945

## Technical characteristics

| | |
|---|---|
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥500 |

## Material properties

| | |
|---|---|
| Material (insert) | Polycarbonate (PC) |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Silver plated |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |

## Specifications and approvals

| | |
|---|---|
| Specifications | IEC 60664-1<br>IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076<br>UL 2237 PVVA2.E318390<br>CSA-C22.2 No. 182.3 PVVA8.E318390 |
| Approvals | DNV GL |

## Commercial data

| | |
|---|---|
| Packaging size | 1 |
| Net weight | 111.06 g |
| Country of origin | China |
| European customs tariff number | 85366990 |
| GTIN | 5713140186293 |
| ETIM | EC000438 |
| eCl@ss | 27440205 Contact insert for industrial connectors |


HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com