

DEUTSCH | DEUTSCH DT, DEUTSCH DTP

TE Internal #: DTP06-2S

Housing for Female Terminals, Wire-to-Wire, 2 Position, .264 in [6.71 mm] Centerline, Sealable, Gray, Wire & Cable, Power &

Signal, Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DTP Housings



Connector System: Wire-to-Wire

Number of Positions: 2

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 6.71 mm [.264 in]

Sealable: Yes

All DEUTSCH DTP Housings (34)

Features

Product Type Features

Troduct Type reduces	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Blank Cavity Position	0
Number of Positions	2
Number of Rows	1
Electrical Characteristics	
Operating Voltage	200 VAC

12 V, 24 V, 48 V

180°

Nominal Voltage Architecture

Body Features

Cable Exit Angle



Primary Product Color	Gray
Contact Features	
Contact Size	Size 12
Contact Type	Socket
Mating Pin Diameter	2.39 mm[.094 in]
Contact Current Rating (Max)	25 A
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA GF
Centerline (Pitch)	6.71 mm[.264 in]
Dimensions	
Connector Height	18.06 mm[.711 in]
Product Width	18.59 mm[.732 in]
Product Length	34.65 mm[1.364 in]
Compatible Insulation Diameter Range	3.4 - 4.32 mm[.13417 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 - 125 °C[-67 - 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Degree of Protection	IP68
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	20mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	1200



Packaging Method Box

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # DTP2S-BT BOOT, 2P, PLG, ST, GRY



TE Part # 1062-12-0144 SOC, SF, SIZE 12, 12-14, AU/SN



TE Part # CAT-D48-SP729 **DEUTSCH Sealing Plugs**



SOC, SF, SIZE 12, 10, NI/NI




TE Part # 1062-12-0166 SOC, SF, SIZE 12, 12-14, NI/SN



Also in the Series | DEUTSCH DT





Position Assurance(74)







Connector Seals & Cavity Plugs(6)



Connector Strain Relief(28)



Insertion & Extraction Tools(3)




Other Automotive Connector Accessories(27)



Also in the Series | DEUTSCH DTP





Automotive Connector Locks & Position Assurance(4)



Automotive Housings(34)



Connector Backshells(1)



Insertion & Extraction Tools(3)



PCB Headers & Receptacles(4)

Customers Also Bought



DEUTSCH DT Plug Connectors











Documents

Product Drawings

PLG, 2P, GRY, N

English

CAD Files

3D PDF

3D

Customer View Model



ENG_CVM_CVM_DTP06-2S_99_c-dtp06-2s-99.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DTP06-2S_99_c-dtp06-2s-99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DTP06-2S_99_c-dtp06-2s-99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Engineering Report

English

Agency Approvals

UL Report

English