General Purpose Transistor
PNP Silicon

PZT3906T1G

Features

- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

ON Semiconductor®

www.onsemi.com

MAXIMUM RATINGS


Rating	Symbol	Value	Unit
Collector − Emitter Voltage	V_{CEO}	−40	Vdc
Collector − Base Voltage	V_{CBO}	−40	Vdc
Emitter − Base Voltage	V_{EBO}	−5.0	Vdc
Collector Current − Continuous	I_C	−200	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation (Note 1) T_A = 25°C	P_D	1.5 12	W mW/°C
Thermal Resistance Junction−to−Ambient (Note 1)	$R_{\theta JA}$	83.3	°C/W
Thermal Resistance Junction−to−Lead #4	$R_{\theta JA}$	35	°C/W
Junction and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


1. FR−4 with 1 oz and 713 mm^2 of copper area.





SOT−223
CASE 318E

MARKING DIAGRAM



2A	= Specific Device Code
A	= Assembly Location
Y	= Year
W	= Work Week
▪	= Pb−Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
PZT3906T1G	SOT−223 (Pb−Free)	1000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2006

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS (Note 2)				
Collector – Emitter Breakdown Voltage (Note 2) (I_C = −1.0 mAdc, I_B = 0)	$V_{(BR)CEO}$	−40	–	Vdc
Collector – Base Breakdown Voltage (I_C = −10 μAdc, I_E = 0)	$V_{(BR)CBO}$	−40	–	
Emitter – Base Breakdown Voltage (I_E = −10 μAdc, I_C = 0)	$V_{(BR)EBO}$	−5.0	–	
Base Cutoff Current (V_{CE} = −30 Vdc, V_{EB} = −3.0 Vdc)	I_{BL}	–	−50	nAdc
Collector Cutoff Current (V_{CE} = −30 Vdc, V_{EB} = −3.0 Vdc)	I_{CEX}	–	−50	
ON CHARACTERISTICS (Note 2)				
DC Current Gain (I_C = −0.1 mAdc, V_{CE} = −1.0 Vdc) (I_C = −1.0 mAdc, V_{CE} = −1.0 Vdc) (I_C = −10 mAdc, V_{CE} = −1.0 Vdc) (I_C = −50 mAdc, V_{CE} = −1.0 Vdc) (I_C = −100 mAdc, V_{CE} = −1.0 Vdc)	H_{FE}	 60 80 100 60 30	 – – 300 – –	–
Collector – Emitter Saturation Voltage (I_C = −10 mAdc, I_B = −1.0 mAdc) (I_C = −50 mAdc, I_B = −5.0 mAdc)	$V_{CE(sat)}$	 – –	 −0.25 −0.4	Vdc
Base – Emitter Saturation Voltage (I_C = −10 mAdc, I_B = −1.0 mAdc) (I_C = −50 mAdc, I_B = −5.0 mAdc)	$V_{BE(sat)}$	 −0.65 –	 −0.85 −0.95	
SMALL– SIGNAL CHARACTERISTICS				
Current – Gain – Bandwidth Product (I_C = −10 mAdc, V_{CE} = −20 Vdc, f = 100 MHz)	f_T	250	–	MHz
Output Capacitance (V_{CB} = −5.0 Vdc, I_E = 0, f = 1.0 MHz)	C_{obo}	–	4.5	pF
Input Capacitance (V_{EB} = −0.5 Vdc, I_C = 0, f = 1.0 MHz)	C_{ibo}	–	10	
Input Impedance (I_C = −1.0 mAdc, V_{CE} = −10 Vdc, f = 1.0 kHz)	h_{ie}	2.0	12	kΩ
Voltage Feedback Ratio (I_C = −1.0 mAdc, V_{CE} = −10 Vdc, f = 1.0 kHz)	h_{re}	0.1	10	X 10^{-4}
Small – Signal Current Gain (I_C = −1.0 mAdc, V_{CE} = −10 Vdc, f = 1.0 kHz)	h_{fe}	100	400	–
Output Admittance (I_C = −1.0 mAdc, V_{CE} = −10 Vdc, f = 1.0 kHz)	h_{oe}	3.0	60	μmhos
Noise Figure (I_C = −100 μAdc, V_{CE} = −5.0 Vdc, R_S = 1.0 kΩ, f = 1.0 kHz)	NF	–	4.0	dB
SWITCHING CHARACTERISTICS				
Delay Time (V_{CC} = −3.0 Vdc, V_{BE} = 0.5 Vdc, I_C = −10 mAdc, I_{B1} = −1.0 mAdc)	t_d	–	35	ns
Rise Time	t_r	–	35	
Storage Time (V_{CC} = −3.0 Vdc, I_C = −10 mAdc, I_{B1} = I_{B2} = −1.0 mAdc)	t_s	–	225	
Fall Time	t_f	–	75	

2. Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.




Figure 1. Delay and Rise Time Equivalent Test Circuit




Figure 2. Storage and Fall Time Equivalent Test Circuit

* Total shunt capacitance of test jig and connectors

TYPICAL TRANSIENT CHARACTERISTICS

$T_J = 25°C$
$T_J = 125°C$




Figure 3. Capacitance




Figure 4. Charge Data




Figure 5. Turn−On Time




Figure 6. Fall Time

TYPICAL AUDIO SMALL−SIGNAL CHARACTERISTICS
NOISE FIGURE VARIATIONS

(V_{CE} = −5.0 Vdc, T_A = 25°C, Bandwidth = 1.0 Hz)




Figure 7.




Figure 8.

h PARAMETERS

(V_{CE} = −10 Vdc, f = 1.0 kHz, T_A = 25°C)




Figure 9. Current Gain




Figure 10. Output Admittance




Figure 11. Input Impedance




Figure 12. Voltage Feedback Ratio

TYPICAL STATIC CHARACTERISTICS




Figure 13. DC Current Gain




Figure 14. Collector Saturation Region




Figure 15. “ON” Voltages




Figure 16. Temperature Coefficients

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales