

PP-V4-CA-USB2B/USB2A-PP/IP20-P-P-STR-1.0



Part number	09 45 445 4911
Specification	PP-V4-CA-USB2B/USB2A-PP/IP20-P-P-STR-1.0
HARTING eCatalogue	https://b2b.harting.com/09454454911

Image is for illustration purposes only. Please refer to product description.

Identification

Category	System cabling
Series	HARTING PushPull (V4)
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING PushPull (V4) USB 2.0 Type B
Connector 1 Connector 2	

Version

Cable length	1 m
Number of cores	4
Core structure	2x AWG 26/7 2x AWG 24/11
Shielding	Shielded

Technical characteristics

Rated current	1.5 A
Rated voltage	30 V DC
Data rate	480 Mbit/s
Insulation resistance	$> 1.6 \times 10^6 \Omega$
Contact resistance	≤30 mΩ
Limiting temperature	-40 +85 °C



Technical characteristics

Insertion force	≤35 N
Withdrawal force	≥15 N
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 IP67
Cable diameter	4.9 mm
Test voltage U _{r.m.s.}	0.5 kV (contact-contact) 0.5 kV (contact-ground)
Impedance	90 Ω ±15 %

Material properties

Material (contacts) Copper alloy Surface (contacts) Sn over Ni Termination side Au over Ni Mating side Material (cable) PVC Colour (cable) Black Material (overmoulding) Polyamide (PA) Colour (overmoulding) Black Material flammability class acc. to UL 94 V-0	Material (insert)	Liquid crystal polymer (LCP)
Surface (contacts) Au over Ni Mating side Material (cable) PVC Colour (cable) Black Material (overmoulding) Polyamide (PA) Colour (overmoulding) Black	Material (contacts)	Copper alloy
Colour (cable) Material (overmoulding) Polyamide (PA) Colour (overmoulding) Black	Surface (contacts)	
Material (overmoulding) Polyamide (PA) Colour (overmoulding) Black	Material (cable)	PVC
Colour (overmoulding) Black	Colour (cable)	Black
	Material (overmoulding)	Polyamide (PA)
Material flammability class acc. to UL 94 V-0	Colour (overmoulding)	Black
	Material flammability class acc. to UL 94	V-0
RoHS compliant	RoHS	compliant
ELV status compliant	ELV status	compliant
China RoHS e	China RoHS	е
REACH Annex XVII substances Not contained	REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances Not contained	REACH ANNEX XIV substances	Not contained
REACH SVHC substances Not contained	REACH SVHC substances	Not contained
California Proposition 65 substances Yes	California Proposition 65 substances	Yes
California Proposition 65 substances Naphthalene	California Proposition 65 substances	Naphthalene

Specifications and approvals

Specifications	IEC 61076-3-106 Variant 4 (V4)	
----------------	--------------------------------	--

Commercial data

Packaging size	1
Net weight	69.25 g

Product data sheet 09 45 445 4911 PP-V4-CA-USB2B/USB2A-PP/IP20-P-P-STR-1.0



Commercial data

Country of origin	Malaysia
European customs tariff number	85444290
GTIN	5713140262898
ETIM	EC002599
eCl@ss	27060390 Ready-made data cable (unspecified)