



GRACE INERTIA 3.5

TE Internal #: 2-1565086-3

Rectangular Power Connectors, Housing, Receptacle, Wire-to-Wire,
3 Position, 3.5 mm [.138 in] Centerline, Wire & Cable, UL 94V-0,
GRACE INERTIA 3.5

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > STD Temp GRACE INERTIA Cap



Rectangular Power Connector Type: **Housing**
Connector & Housing Type: **Receptacle**
Connector System: **Wire-to-Wire**
Number of Positions: **3**
Centerline (Pitch): **3.5 mm [.138 in]**

[All STD Temp GRACE INERTIA Cap \(24\)](#)

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	3
Number of Power Positions	0
Number of Signal Positions	0
Number of Rows	1

Electrical Characteristics

Operating Voltage	300 VAC
-------------------	---------



Body Features

Connector & Keying Code	C
-------------------------	---

Contact Features

Contact Layout	Inline
Contact Base Material	Copper Alloy
Contact Retention Within Housing	Without
Contact Type	Tab

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Inertia Locking, Latch, Locking Latch
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Centerline (Pitch)	3.5 mm[.138 in]
Housing Color	Blue
Housing Material	Nylon 6/6 GF

Dimensions

Connector Height	9.3 mm[.366 in]
Product Length	12.55 mm[.493 in]

Usage Conditions

Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire



Packaging Features

Packaging Quantity	300
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-G7534-T111
GRACE INERTIA Tab



TE Part # 2-1565082-3
GRACE INERTIA CONNECTOR 3.5 3P



TE Part # 1565090-1
GRACE INERTIA CONNECTOR 3.5 3P



TE Part # 5-1565086-1
GRACE INERTIA CONNECTOR 3.5W 3POS CAP



TE Part # 5-1565090-1
GIC 3.5 3P DBL LOCK PLATE PBT (BLACK)

TE Part # 1729279-1
EXTRACTION TOOL FOR GIC 3.5 CONN.

Also in the Series

GRACE INERTIA 3.5

Connector Contacts(4)

Connector Hardware(4)

Insertion & Extraction Tools(1)

Rectangular Power Connectors(63)

Customers Also Bought

TE Part # 177899-1
POWER DBL LOCK PLUG HSG 3P

TE Part # 1565079-1
GRACE INERTIA 3.5 REC CONTACT(L)

TE Part # 1565080-1
GRACE INERTIA 3.5 TAB CONTACT(L)

TE Part # 1744036-2
02P ECONOMY POWER .200 CL HSG

TE Part # 175019-1
187 PL EX FLAG REC. 22-16AWG PTBR

TE Part # 1-178708-1
187 SLEEV PL EX FLAG NAT

Documents

Product Drawings

GRACE INERTIA CONNECTOR 3.5 3P

English

CAD Files

3D PDF

3D



Customer View Model

[ENG_CVM_CVM_2-1565086-3_C.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-1565086-3_C.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-1565086-3_C.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

English

[1-1773883-5 GRACE INERTIA connector quick reference guide](#)

English

Product Specifications

[Product Specification](#)

English

[Product Specification](#)

English

Instruction Sheets

[Extraction Tool for GIC 3.5 Conn.](#)

Japanese

[Instruction Sheet \(non U.S.\)](#)

Japanese

Agency Approvals

[UL Report](#)

English