

Part Number : 190060019

Series Number : 19006

Product Category : Quick Disconnects

Product Description : Avikrimp Quick Disconnect, Female Flag, for 10-12 AWG (5.00-3.30mm<sup>2</sup>) Wire, Tab 6.35 x 0.81mm, Yellow

Status : Active

Engineering Number : C-5211

---

## Documents & Resources

### Drawings

Drawing 190060019\_sd.pdf

### 3D Models and Design Files

3D Model 190060019\_stp.zip

### Specifications

Product Specification PS-19902-011-001.pdf

Product Specification PS-19902-013-001.pdf

Product Specification PS-19902-014-001.pdf

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Compliant with Exemption 44
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

Status	Active
Category	Quick Disconnects
Series	19006
Description	Avikrimp Quick Disconnect, Female Flag, for 10-12 AWG (5.00-3.30mm <sup>2</sup> ) Wire, Tab 6.35 x 0.81mm, Yellow
Product Family	Standard Quick-Disconnect Terminals
Product Name	Avikrimp
Type	Quick Disconnect
UPC	800753031203

#### Agency

CSA	LR18689
UL	E79133

#### Electrical

Voltage - Maximum	600V
-------------------	------

#### Physical

Barrel Type	Closed
Color - Resin	Yellow
Flammability	94V-2
Gender	Female
Glow-Wire Capable	Yes
Insulated	Fully
Insulation	Nylon (PA)
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Tin

Material - Plating Termination	Tin
Material - Resin	Nylon
Net Weight	1.862/g
Orientation	Flag
Packaging Type	Bag
Polarized to Mating Part	No
Tab Thickness	0.81mm
Tab Width	6.35mm
Temperature Range - Operating	-65° to +105°C
Wire Insulation Diameter	6.30mm max.
Wire Size (AWG)	10 (105 strands), 12 (65 strands)

## Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

---

## Application Tooling

### Global

Description	Part Number
Hand Crimp Tool for AviKrimp Fully Insulated and Insulated Quick Disconnect Flags, 10-12 AWG	<u>640018800</u>

---

This document was generated on Jun 05, 2024