

Si/SiC Hybrid Module – EliteSiC, 3 Channel Symmetric Boost 1000 V, 200 A IGBT, 1200 V, 60 A SiC Diode, Q2 Package

NXH600B100H4Q2F2PG, NXH600B100H4Q2F2SG, NXH600B100H4Q2F2SG-R



PIM44, 93x47 (PRESS FIT)
CASE 180HF



PIM44, 93x47 (SOLDER PIN)
CASE 180HE

The NXH600B100H4Q2 is a Si/SiC Hybrid three channel symmetric boost module. Each channel contains two 1000 V, 200 A IGBTs, and two 1200 V, 60 A SiC diodes. The module contains an NTC thermistor.

Features

- Extremely Efficient Trench with Field Stop Technology
- Low Switching Loss Reduces System Power Dissipation
- Module Design Offers High Power Density
- Low Inductive Layout
- Low Package Height
- Pb−Free, Halogen Free/BFR Free and RoHS Compliant

Typical Applications

- Solar Inverters
- Uninterruptable Power Supplies Systems






Figure 1. NXH600B100H4Q2F2 Schematic Diagram

MARKING DIAGRAM



NXH600B100H4Q2F2xG	= Device Code
X	= P or S
G	= Pb−Free Package
AT	= Assembly & Test Site Code
YYWW	= Year and Work Week Code

PIN CONNECTIONS



ORDERING INFORMATION

See detailed ordering and shipping information on page 11 of this data sheet.

© Semiconductor Components Industries, LLC, 2021

ABSOLUTE MAXIMUM RATINGS (Note 1) T_J = 25°C unless otherwise noted

Parameter	Symbol	Value	Unit
IGBT (T11, T21, T12, T22, T13, T23)			
Collector−Emitter Voltage	V_{CES}	1000	V
Gate−Emitter Voltage Positive Transient Gate − Emitter Voltage (tpulse = 5 μs, D < 0.10)	V_{GE}	±20 30	V
Continuous Collector Current @ T_c = 80°C	I_C	192	A
Pulsed Peak Collector Current @ T_c = 80°C (T_J = 175°C)	$I_{C(Pulse)}$	576	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	511	W
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature (Note 2)	T_{JMAX}	175	°C
IGBT INVERSE DIODE (D11, D21, D12, D22, D13, D23)			
Peak Repetitive Reverse Voltage	V_{RRM}	1200	V
Continuous Forward Current @ T_c = 80°C	I_F	66	A
Repetitive Peak Forward Current (T_J = 175°C)	I_{FRM}	198	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	101	W
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C
SILICON CARBIDE SCHOTTKY DIODE (D31, D41, D32, D42, D33, D43)			
Peak Repetitive Reverse Voltage	V_{RRM}	1200	V
Continuous Forward Current @ T_c = 80°C	I_F	73	A
Repetitive Peak Forward Current (T_J = 175°C)	I_{FRM}	219	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	217	W
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C
THERMAL PROPERTIES			
Operating Temperature under Switching Condition	T_{VJOP}	−40 to 150	°C
Storage Temperature Range	T_{stg}	−40 to 125	°C
INSULATION PROPERTIES			
Isolation Test Voltage, t = 1 s, 50 Hz	V_{is}	4000	V_{RMS}
Creepage Distance		12.7	mm
Comparative Tracking Index	CTI	>600	

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS, RECOMMENDED OPERATING RANGES and/or APPLICATION INFORMATION for Safe Operating parameters.
2. Qualification at 175°C per discrete TO247.

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (continued)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
IGBT (T11, T21, T12, T22, T13, T23) CHARACTERISTICS						
Collector−Emitter Breakdown Voltage	V_{GE} = 0 V, I_C = 1 mA	$V_{(BR)CES}$	1000	1165	–	V
Collector−Emitter Cutoff Current	V_{GE} = 0 V, V_{CE} = 1000V	I_{CES}	–	–	10	μA
Collector−Emitter Saturation Voltage	V_{GE} = 15 V, I_C = 200 A, T_J = 25°C	$V_{CE(sat)}$	–	1.69	2.3	V
	V_{GE} = 15 V, I_C = 200 A, T_J = 175°C		–	2.15	–	
Gate−Emitter Threshold Voltage	V_{GE} = V_{CE}, I_C = 200 mA	$V_{GE(TH)}$	3.8	4.75	6.6	V
Gate Leakage Current	V_{GE} = ±20 V, V_{CE} = 0 V	I_{GES}	–	–	±1	μA
Internal Gate Resistor		r_g	–	2	–	Ω
Turn−on Delay Time	T_J = 25°C V_{CE} = 600 V, I_C = 50A V_{GE} = −9 V, 15 V, R_{gon} = 6 Ω, R_{goff} = 6 Ω	$t_{d(on)}$	–	111	–	ns
Rise Time		t_r	–	15	–	
Turn−off Delay Time		$t_{d(off)}$	–	338	–	
Fall Time		t_f	–	113	–	
Turn−on Switching Loss per Pulse		E_{on}	–	460	–	μJ
Turn off Switching Loss per Pulse		E_{off}	–	1930	–	
Turn−on Delay Time	T_J = 125°C V_{CE} = 600 V, I_C = 50 A V_{GE} = −9 V, 15 V, R_{gon} = 6 Ω, R_{goff} = 6 Ω	$t_{d(on)}$	–	111	–	ns
Rise Time		t_r	–	17	–	
Turn−off Delay Time		$t_{d(off)}$	–	406	–	
Fall Time		t_f	–	142	–	
Turn−on Switching Loss per Pulse		E_{on}	–	660	–	μJ
Turn off Switching Loss per Pulse		E_{off}	–	2860	–	
Input Capacitance	V_{CE} = 20 V, V_{GE} = 0 V, f = 1 MHz	C_{ies}	–	13256	–	pF
Output Capacitance		C_{oes}	–	456	–	
Reverse Transfer Capacitance		C_{res}	–	78	–	
Total Gate Charge	V_{CE} = 600 V, I_C = 40 A, V_{GE} = −15V~15 V	Q_g	–	766	–	nC
Thermal Resistance − Chip−to−Heatsink	Thermal grease, Thickness = 2.1 Mil ±2% λ = 2.87 W/mK	R_{thJH}	–	0.45	–	K/W
Thermal Resistance − Chip−to−Case		R_{thJC}	–	0.186	–	K/W
IGBT INVERSE DIODE (D11, D21, D12, D22, D13, D23) CHARACTERISTICS						
Diode Forward Voltage	I_F = 50 A, T_J = 25 °C	V_F	–	1.10	1.55	V
	I_F = 50 A, T_J = 175 °C		–	0.975	–	
Thermal Resistance − Chip−to−Heatsink	Thermal grease, Thickness = 2.1 Mil ±2% λ = 2.87 W/mK	R_{thJH}	–	0.98	–	K/W
Thermal Resistance − Chip−to−Case		R_{thJC}	–	0.65	–	K/W
DIODES (D31, D41, D32, D42, D33, D43) CHARACTERISTICS						
Diode Forward Voltage	I_F = 60 A, T_J = 25°C	V_F	–	1.54	1.85	V
	I_F = 60 A, T_J = 175°C		–	2.27	–	
Reverse Recovery Time	T_J = 25°C V_{CE} = 600 V, I_C = 50 A V_{GE} = −9 V, 15 V, R_{gon} = 6 Ω	t_{rr}	–	13	–	ns
Reverse Recovery Charge		Q_{rr}	–	93	–	nC
Peak Reverse Recovery Current		I_{RRM}	–	11	–	A
Peak Rate of Fall of Recovery Current		di/dt	–	2767	–	A/μs
Reverse Recovery Energy		E_{rr}	–	45	–	μJ

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (continued)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Reverse Recovery Time	T_J = 125 °C V_{CE} = 600 V, I_C = 50 A V_{GE} = −9 V, 15 V, R_{gon} = 6 Ω	t_{rr}	–	12	–	ns
Reverse Recovery Charge		Q_{rr}	–	90	–	nC
Peak Reverse Recovery Current		I_{RRM}	–	11	–	A
Peak Rate of Fall of Recovery Current		di/dt	–	2287	–	A/μs
Reverse Recovery Energy		E_{rr}	–	32	–	μJ
Thermal Resistance − Chip−to−Heatsink	Thermal grease, Thickness = 2.1 Mil±2% λ = 2.87 W/mK	R_{thJH}	–	0.68	–	K/W
Thermal Resistance − Chip−to−Case		R_{thJC}	–	0.438	–	K/W

THERMISTOR CHARACTERISTICS

Nominal Resistance	T = 25°C	R_{25}	–	22	–	kΩ
Nominal Resistance	T = 100°C	R_{100}	–	1504	–	Ω
Deviation of R25		ΔR/R	−1	–	1	%
Power Dissipation		P_D	–	187.5	–	mW
Power Dissipation Constant			–	1.5	–	mW/K
B−value	B (25/100), tolerance ±1%		–	3980	–	K

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL CHARACTERISTICS − IGBT, INVERSE DIODE AND BOOST DIODE




Figure 2. Typical Output Characteristics




Figure 3. Typical Output Characteristics




Figure 4. Transfer Characteristics




Figure 5. Saturation Voltage Characteristic




Figure 6. Boots Diode Forward Characteristics




Figure 7. Inverse Diode Forward Characteristics

TYPICAL CHARACTERISTICS − IGBT AND BOOST DIODE




Figure 8. Typical Turn On Loss vs. IC




Figure 9. Typical Turn Off Loss vs. I_C




Figure 10. Typical Turn On Loss vs. Rg




Figure 11. Typical Turn Off Loss vs. Rg




Figure 12. Typical Reverse Recovery Energy Loss vs. I_C




Figure 13. Typical Reverse Recovery Energy Loss vs. Rg

TYPICAL CHARACTERISTICS − IGBT AND BOOST DIODE (CONTINUED)




Figure 14. Typical Turn−Off Switching Time vs. I_C




Figure 15. Typical Turn−On Switching Time vs. I_C




Figure 16. Typical Turn−Off Switching Time vs. Rg




Figure 17. Typical Turn−On Switching Time vs. Rg




Figure 18. Typical Reverse Recovery Time vs. Rg




Figure 19. Typical Reverse Recovery Charge vs. Rg

TYPICAL CHARACTERISTICS − IGBT AND BOOST DIODE (CONTINUED)




Figure 20. Typical Reverse Recovery Peak Current vs. Rg




Figure 21. Typical di/dt vs. Rg




Figure 22. Typical Reverse Recovery Time vs. Ic




Figure 23. Typical Reverse Recovery Charge vs. Ic




Figure 24. Typical Reserve Recovery Current vs. Ic




Figure 25. Typical di/dt vs. Ic

TYPICAL CHARACTERISTICS − IGBT




Figure 26. RBSOA




Figure 27. Capacitance Charge




Figure 28. Gate Voltage vs. Gate Charge




Figure 29. Temperature vs NTC Value

TYPICAL CHARACTERISTICS − IGBT, INVERSE DIODE AND BOOST DIODE




Figure 30. Transient Thermal Impedance (IGBT)




Figure 31. Transient Thermal Impedance (BOOST DIODE)





Figure 32. Transient Thermal Impedance (INVERSE DIODE)

ORDERING INFORMATION


Device Order Number	Marking	Package	Shipping
NXH600B100H4Q2F2SG, NXH600B100H4Q2F2SG−R	NXH600B100H4Q2F2SG, NXH600B100H4Q2F2SG−R	Q2BOOST − Case 180HE (Pb−Free and Halide−Free Solder Pins)	12 Units / Blister Tray
NXH600B100H4Q2F2PG	NXH600B100H4Q2F2PG	Q2BOOST − Case 180HF (Pb−Free and Halide−Free Press Fit Pins)	12 Units / Blister Tray

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS




PIM44, 93x47 (SOLDER PIN)
CASE 180HE
ISSUE O


DATE 21 OCT 2021



TOP VIEW



END VIEW



SIDE VIEW

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	17.00	17.40	17.80
A2	11.70	12.00	12.30
A3	4.40	4.70	5.00
A4	16.40	16.70	17.00
b	0.95	1.00	1.05
D	92.90	93.00	93.10
D1	104.45	104.75	105.05
D2	81.80	82.00	82.20
D3	106.90	107.20	107.50
E	46.70	47.00	47.30
E1	44.10	44.40	44.70
E2	38.80	39.00	39.20
P	5.40	5.50	5.60
P1	10.60	10.70	10.80
P2	1.80	2.00	2.20

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009
2. CONTROLLING DIMENSION : MILLIMETERS
3. DIMENSIONS b AND b1 APPLY TO THE PLATED TERMINALS AND ARE MEASURED AT DIMENSION A1
4. PIN POSITION TOLERANCE IS ± 0.4mm
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES

NOTE 4

PIN	PIN POSITION		PIN	PIN POSITION	
	X	Y		X	Y
1	0.00	0.00	23	11.40	22.00
2	2.80	0.00	24	13.90	22.00
3	0.00	9.20	25	31.45	22.00
4	2.80	9.20	26	33.95	22.00
5	5.60	9.20	27	36.95	23.70
6	5.00	12.00	28	42.65	22.00
7	20.00	10.00	29	53.40	22.00
8	20.00	12.50	30	59.10	23.70
9	25.35	10.00	31	62.10	22.00
10	25.35	12.50	32	64.60	22.00
11	39.75	9.20	33	0.00	34.40
12	40.35	12.00	34	0.00	36.90
13	42.55	9.20	35	20.00	34.40
14	45.35	9.20	36	20.00	36.90
15	50.70	9.20	37	25.35	34.40
16	53.50	9.20	38	25.35	36.90
17	56.30	9.20	39	45.35	34.40
18	55.70	12.00	40	45.35	36.90
19	70.70	10.00	41	50.70	34.40
20	70.70	12.50	42	50.70	36.90
21	2.70	22.00	43	70.70	34.40
22	8.40	23.70	44	70.70	36.90


onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2021


PIM44, 93x47 (SOLDER PIN)
CASE 180HE
ISSUE O

DATE 21 OCT 2021

GENERIC
MARKING DIAGRAM*




FRONTSIDE MARKING



BACKSIDE MARKING

XXXXX = Specific Device Code
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code



RECOMMENDED
MOUNTING PATTERN

* For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON39002H**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**PIM44, 93x47 (SOLDER PIN)**	**PAGE 2 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.


© Semiconductor Components Industries, LLC, 2021

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS




PIM44, 93x47 (PRESS FIT)
CASE 180HF
ISSUE O


DATE 26 OCT 2021



TOP VIEW



END VIEW



SIDE VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009
2. CONTROLLING DIMENSION : MILLIMETERS
3. DIMENSIONS b AND b1 APPLY TO THE PLATED TERMINALS AND ARE MEASURED AT DIMENSION A1
4. PIN POSITION TOLERANCE IS ± 0.4mm
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	16.90	17.30	17.70
A1	14.18(REF)		
A2	11.70	12.00	12.30
A3	4.40	4.70	5.00
A4	16.40	16.70	17.00
b	1.61	1.66	1.71
b1	0.75	0.80	0.85
D	92.90	93.00	93.10
D1	104.45	104.75	105.05
D2	81.80	82.00	82.20
D3	106.90	107.20	107.50
E	46.70	47.00	47.30
E1	44.10	44.40	44.70
E2	38.80	39.00	39.20
P	5.40	5.50	5.60
P1	10.60	10.70	10.80
P2	1.80	2.00	2.20

NOTE 4

PIN	PIN POSITION		PIN	PIN POSITION	
	X	Y		X	Y
1	0.00	0.00	23	11.40	22.00
2	2.80	0.00	24	13.90	22.00
3	0.00	9.20	25	31.45	22.00
4	2.80	9.20	26	33.95	22.00
5	5.60	9.20	27	36.95	23.70
6	5.00	12.00	28	42.65	22.00
7	20.00	10.00	29	53.40	22.00
8	20.00	12.50	30	59.10	23.70
9	25.35	10.00	31	62.10	22.00
10	25.35	12.50	32	64.60	22.00
11	39.75	9.20	33	0.00	34.40
12	40.35	12.00	34	0.00	36.90
13	42.55	9.20	35	20.00	34.40
14	45.35	9.20	36	20.00	36.90
15	50.70	9.20	37	25.35	34.40
16	53.50	9.20	38	25.35	36.90
17	56.30	9.20	39	45.35	34.40
18	55.70	12.00	40	45.35	36.90
19	70.70	10.00	41	50.70	34.40
20	70.70	12.50	42	50.70	36.90
21	2.70	22.00	43	70.70	34.40
22	8.40	23.70	44	70.70	36.90


onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2021


PIM44, 93x47 (PRESS FIT)
CASE 180HF
ISSUE O

DATE 26 OCT 2021

GENERIC
MARKING DIAGRAM*



XXXXX = Specific Device Code
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code



RECOMMENDED
MOUNTING PATTERN

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

www.onsemi.com

© Semiconductor Components Industries, LLC, 2021

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales