ATGBICS

# ATGBICS FWLF1634RL32 Finisar Compatible Transceiver DWDM Ch32 SFP+ 4.25GBase (1551.72nm, SMF, 80km, LC, DOM)

**Brand :** ATGBICS

**Product code:** FWLF1634RL32-C

**Product name :** FWLF1634RL32 Finisar Compatible Transceiver DWDM Ch32 SFP+ 4.25GBase (1551.72nm, SMF, 80km, LC, DOM)



FWLF1634RL32 Finisar Compatible Transceiver DWDM Ch32 SFP+ 4.25GBase (1551.72nm, SMF, 80km, LC, DOM)
ATGBICS FWLF1634RL32 Finisar Compatible Transceiver DWDM Ch32 SFP+ 4.25GBase (1551.72nm, SMF, 80km, LC, DOM). SFP transceiver type: Fiber optic, Maximum data transfer rate: 4250 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box

RoHS

| Performance | |
|---|---|
| SFP transceiver type * | Fiber optic |
| Maximum data transfer rate * | 4250 Mbit/s |
| Interface type * | SFP+ |
| Single-mode fiber (SMF) supported | ✓ |
| Multi-mode fiber (MMF) supported | ✗ |
| Fiber optic connector | LC |
| SFP transceiver standard | DWDM |
| Maximum transfer distance | 80000 m |
| Wavelength | 1551.72 nm |
| Coarse Wavelength Division Multiplexing (CWDM) | ✓ |
| Ethernet LAN | ✓ |
| Ethernet interface type | 4.25 Gigabit Ethernet |
| Digital Diagnostics Monitoring (DDM) | ✓ |

| Features | |
|---|---|
| Product colour | Silver |
| Housing material | Metal |
| Plug and Play | ✓ |
| Hot-swap | ✓ |
| Easy to install | ✓ |
| Country of origin | United Kingdom |
| Brand compatibility | Finisar |
| Certification | CE, FCC, RoHS |

| Power | |
|---|---|
| Input voltage | 3.3 V |
| Maximum voltage | 3.5 V |
| Power consumption (typical) | 1 W |

| Operational conditions | |
|---|---|
| Minimum operating temperature | -5 °C |
| Maximum operating temperature | 70 °C |
| Operating temperature (T-T) | -5 - 70 °C |
| Storage temperature (T-T) | -40 - 85 °C |
| Operating relative humidity (H-H) | 0 - 95% |
| Storage relative humidity (H-H) | 0 - 95% |

| Weight & dimensions | |
|---|---|
| Width | 13.4 mm |
| Depth | 56.5 mm |
| Height | 8.5 mm |
| Weight | 20 g |

| Packaging data | |
|---|---|
| Number of products included | 1 pc(s) |
| Package type | Box |

| Technical details | |
|---|---|
| Sustainability compliance | ✓ |
| Sustainability certificates | RoHS |
| Doesn't contain | Lead |



5056468765833

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-JUN-2024. Prints or copies of Information are only valid on the printed Publication date