

COMPACT TDX PANEL PROTECTOR, 100 kA, 240 VAC UN

CATALOG NUMBER

TDX100C240



CERTIFICATIONS



FEATURES

Built-in features include TD Technology, thermal protection and short circuit current fusing

Compact NEMA®-4 enclosure design can be flush mounted or installed in a small space

LED status indication and voltage-free contacts provide remote status monitoring

100 kA 8/20 μ s maximum surge rating provides protection suitable for main-distribution panels and an extended operational life

PRODUCT ATTRIBUTES

Nominal System Voltage (Un): 240 VAC

Distribution System: 1Ph 2W+G

Max Continuous Operating Voltage (Uc): 276 VAC

Stand-off Voltage: 480 VAC

Frequency: 50 - 60 Hz

Short Circuit Current Rating (SCCR): 200 kA

Nominal Discharge Current (In), IEC: 40 kA 8/20 μ s

Nominal Discharge Current (In), UL: 20 kA 8/20 μ s

Max Discharge Current (Imax), Per Phase: 100 kA 8/20 μ s

Impulse Current (Iimp), Per Mode: 12.5 kA 10/350 μ s

Voltage Protection Rating (VPR), L-N: 1000 V @ 3 kA; 1800 V @ 20 kA

Protection Modes: L-N;L-PE;N-PE

Remote Contacts: Yes

Status Indication: LED

Surge Counter: No

Technology: Over-current fusing;TD technology with thermal disconnect

Lead Size imperial: #10

Ground Lead Length: 36

Temperature: -40 to 176 °F

Enclosure Material: Metal

Enclosure Rating: IP 65;NEMA®-4

Mounting: 3/4" straight nipple

Depth (D): 3.07"

Height (H): 6.02"


Width (W): 3.31"

Unit Weight: 1.76 lb

Certification Details: UL® 1449 Edition 5 Type 1/2, 20 kA Mode

Complies With: ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C;ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 1, 20 kA 8/20 µs, 2 kA 10/350 µs

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



nVent.com

Our powerful portfolio of brands:

TRACER

CADDY ERICO HOFFMAN RAYCHEM SCHROFF